



NOTE: Sweep period for gate closer to be adjusted so that gate will take at least 3 seconds to move from an open position of 70 degrees to a point 3 inches from the latch, measured to the leading edge of the gate.

MRCA Rules Sign
Minimum clearance per city of Malibu
1 6" X 1 6" Stone pilasters with Cross Creek River Rock veneer. Stone available from:
Malibu Stone + Masonry Supply
www.malibustonemasonry.com
310.456.9444

Lever handle to be located no higher than 48" above F.G.; include lock.

Decorative wrought iron gate panels; gate to be self-closing.

NOTE: Maximum allowable force for pushing or pulling gate not to exceed 5lb./ft.

F.G. - Provide 60" of level space on push side of gate

1 0" kick plate (typical - both sides)

Vertical cane bolt and sleeve

ENTRY GATE

SCALE: (see graphic scale)
FILE: D_ENTRY_GATE_WITH_PILASTERS



REVISIONS	DATE
1.	
2.	
3.	
4.	
5.	
6.	
7.	
8.	

MOUNTAINS RECREATION AND CONSERVATION AUTHORITY
570 WEST AVENUE TWENTY-SIX
LOS ANGELES, CALIFORNIA

ENTRY GATE DETAILS

PROJECT TITLE
LECHUZA BEACH
Malibu California
PROJECT LOCATION:
Lot 1, at Broad Beach Road, across Bonnie Lane

DRAWN BY: LAS
CHECKED BY: LAS
PROJECT NO. Not Applicable
DATE: 12.3.08
SHEET 1 OF 1